



#### **TECHNICAL INFORMATION**

Lumens:	1050
Input Power:	DC:3.2V
Long Life:	20,000 Hours
Unit Color:	Black
Body Type:	Aluminium
LED Chip Type:	SMD
CRI:	>70
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	120°
Color Temperature:	4000K
Dimension:	247x65x210mm
Battery Type:	Ni-Cd 3.2V, 10000mAh Battery
Charging Time:	4 Hours
Working Time:	8 Hours
Solar Panel:	16W



## **SOLAR FLOODLIGHTS | LED LIGHTING**

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

## **FEATURES**

- Solar Powered Floodlight Zero electricity cost.
- Designed with Remote control, Auto and timer function.
- Flexible installation, designed with solar panel with 5 meter wire length
- Solar panel Dimension:350x300x17mm
- Perfectly built for outdoor with Ingress protection of IP65
- Suitable for Pathways, Garden, Patio and similar outdoor environment





# LISTING DETAILS

Commodity Code:	94054110
Ean Code:	3800157645591

# **PACKAGING**

Gross Weight (Kgs):	2.847
Unit CBM:	0.0105
Dimension:	247x65x210mm

#### MASTER BOX PACKAGING

Box Qty:	6
Qty Per Pallet:	180
Length (Box) mm:	100
Width (Box) mm:	300
Height (Box) mm:	350